

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number  
**WO 2004/010819 A1**

(51) International Patent Classification<sup>7</sup>: **A45D 29/02**

(21) International Application Number:  
PCT/BR2003/000091

(22) International Filing Date: 10 July 2003 (10.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
MU8201678-0 29 July 2002 (29.07.2002) BR

(71) Applicant (for all designated States except US): **ZIVI S/A CUTELARIA** [BR/BR]; Rua Visconde de Pelotas, 360, Passo Dareia, 91030-530 Porto Alegre (BR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WURZEL, Paulo, Roberto** [BR/BR]; Rua Nelson de Oliveira Lopes, 370, Vista Alegre, Cachoeirinha-RS (BR).


(74) Agent: **DANNEMANN, SIEMSEN, BIGLER & IPANEMA MOREIRA**; Caixa Postal 2142, Rua Marquês de Olinda, 70, Botafogo, CEP-22251-040 Rio de Janeiro, RJ (BR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: CUTICLE CUTTER



(57) Abstract: A cuticle cutter of the like is described which is of the scissors type. Instruments of this type, especially in beauty salons, require constant cleaning, sharpening and sterilisation. The cutter of the invention facilitates such procedures by permitting the handles (2,21) to be separate from the blades (1, 1'). In the preferred embodiment the blades are snap fitted into the handles and the arrangement is such that on opening the cutters to a maximum surfaces on the handles enter into abutment with the blades in the region of the pivot (6) and further opening cams the blades away from the handles, releasing them without any necessity for manual contact. The blades can then be submitted to the above mentioned procedures and stored for further use.

WO 2004/010819 A1